

SECRET

GIIIIIIID

FZM-2612
14 May 1962

ADDITIONAL STUDIES OF B-58
MISSILE LAUNCH CAPABILITIES

USAF Declass/Release Instructions On File

(TITLE UNCLASSIFIED)

DOWNGRADED AT 12 YEAR
INTERVALS, NOT AUTOMATICALLY
DECLASSIFIED: DOD DIR 5200.10

COPY NO. 9

GD CONTROL NO.
FW/63/100/413

GENERAL DYNAMICS | FORT WORTH

SECRET

SECRET

INTRODUCTION

ORIGINAL PRESENTATION AND SUBSEQUENT DISCUSSIONS HAVE SHOWN STRONG INTEREST IN HIGHER PAYLOADS

- Multiple Passes
- Multiple Sensors
- Lower Development Risk

FULL INVESTIGATION OF INCREASED PAYLOAD, DEMANDS EXAMINATION OF SEVERAL DESIGN AREAS

- Airplane Payload Capability (FZM-2574)
- Missile Capability
- Missile/Aircraft Integration
 - Missile Size and Shape
 - Subsonic and Supersonic Launch

INVESTIGATION WAS IMPLEMENTED BY :

- Wind Tunnel Program for Effect of Missile Size and Shape
- Study of B-58 Engine Improvements for Increased Acceleration Capability
- Booster Design Studies for More Efficient Utilization of Available Weight and Size
- Studies of Improved Guidance/Control Systems

GIHIIID

A0 0922
14 MAY 62


SECRET

SECRET

WIND TUNNEL PROGRAM (APRIL 1962)

OBJECTIVE: To determine the effect of motor diameter and missile shape on the total drag of the airplane with missile at Mach numbers from 0.9 to 2.0

MODELS: Existing 1/40 scale B-58A plus missile with variations in motor diameter, nose cone diameter, center section fairing and boattail fairing length







GIHIIID

AD 0923
14 MAY 62

SECRET

SECRET

WIND TUNNEL RESULTS





GROUP

10 0924
14 MAY 62

SECRET

SECRET

B-58 POWERPLANT STUDY STANDARD DAY







GROUP 1

AD 0925
14 MAY 62

SECRET

SECRET

BOOSTER SPACE ENVELOPE



GROUP D


AD 0926
14 MAY 62

SECRET

SECRET


GD-UTC BOOSTER STUDY

Configuration A
LAUNCH WT. = 48,800*




PROPELLANT WT.	3200*	10,630*	28,554*
TVC FLUID WT.	51*	169*	446*
STAGE WT.	3676*	12,091*	31,549*

Configuration B
LAUNCH WT. = 65,600*



PROPELLANT WT.	4100*	14,420*	38,580*
TVC FLUID WT.	63*	221*	590*
STAGE WT.	4682*	16,284*	42,644*

Configuration C
LAUNCH WT. = 79,000*



PROPELLANT WT.	4620*	18,800*	45,500*
TVC FLUID WT.	73*	290*	690*
STAGE WT.	5248*	21,033*	50,259*


GIHIIID

AD 0927
14 MAY 62

SECRET

SECRET

TYPICAL UTC MOTOR DESIGN



GINN

SECRET

SECRET


SECRET

PAYLOAD CAPABILITIES (AT 100 N.M.I.)

ACCELERATION LIMITS:

J79-5B ENGINES
(PRESENT B-58)

IMPROVED
J79 ENGINES



G D

SECRET

SECRET

SECRET

CONCLUSIONS

LAUNCH VEHICLE SHOULD BE DESIGNED FOR LARGEST BOOSTER
PHYSICALLY COMPATIBLE WITH B-58.

PAYLOADS IN EXCESS OF 2000 LBS. MAY BE ACHIEVED WITH :

- Present B-58 (Mods. $\leq$ \$200,000), Supersonic Launch
- Present Solid Propellant Technology
- Guaranteed Capability (Subsonic Launch) ~ 1800 lbs.

TO ACHIEVE MAXIMUM CAPABILITY REQUIRES CAREFULL BOOSTER/AC INTEGRATION

- Optimization of Both Booster and Aircraft Performance
- Full Utilization of Available Booster Volume

GIHIIID

AD 0930
14 MAY 62

SECRET

SECRET


INTEGRATED GUIDANCE & CONTROL SYSTEM

(BASED ON SYS. UNDER DEVELOPMENT BY UNITED AIRCRAFT)

SYSTEM COMPONENTS

INERTIAL PLATFORM-HIGH PERFORMANCE INERTIAL COMPONENTS.
CELESTIAL ANGLE SENSOR, BODY MOUNTED, NO STAR TRACKING REQUIRED, WIDE ANGLE FIELD
HIGH SPEED DIGITAL COMPUTER. COMPACT, 1 MC CLOCK RATE, 4000 WORD, 30 BITS.
HYPERGOLIC VERNIER PROPULSION. COLD GAS ATTITUDE CONTROL.

SYSTEM OPERATION



GIHIIIIID

AD 0931
14 MAY 62


SECRET

SECRET

UNITED AIRCRAFT GUIDANCE & CONTROL SYSTEM

SYSTEM INTERFACE

- Platform provides velocity and attitude
- Star-angle sensor provides stellar fix for position and azimuth correction
- Attitude control and propulsion system provide stabilization and trajectory adjustment



SYSTEM FEATURES

- AN INTEGRATED *HIGH QUALITY* GUIDANCE CONTROL AND VERNIER PROPULSION SYSTEM
- STELLAR MONITORING FOR *PRECISE* INJECTION AND DE-ORBIT GUIDANCE
 - Capability for accurate guidance without precise knowledge of position and azimuth
 - Requirement for accurate booster termination is relaxed
 - Capability for orbit adjust or orbit transfer
 - Capability for de-orbit and recovery guidance

GIHIIID

AD 0932
14 MAY 62

SECRET

SECRET


STATUS & SCHEDULE

UNITED AIRCRAFT G&C SYSTEM PROGRAM

STATUS

- INTEGRATED SYSTEM DESIGN IN FINAL STAGES
- STAR ANGLE SENSOR AND PLATFORM IN PERFORMANCE EVALUATION
- BREADBOARD COMPUTER UNDERGOING FUNCTIONAL TESTS
- IN PREPARATION FOR TOTAL SYSTEM, IN-ENVIRONMENT, REAL-TIME SIMULATION
- TOTAL SYSTEM SIMULATION WILL PROVIDE REALISTIC ENGINEERING SOLUTIONS THEREBY SPEEDING DEVELOPMENTAL PHASE

SCHEDULE



GIHMD

AD 0933
14 MAY 62

SECRET